**Image Scanner** 

# RICOH fi-8040 Datasheet

☑ Scanner





## Touchpoint for direct information sharing

- "DirectScan" breakthrough.
- Workflow efficiency.
- User experience enhanced.

### "DirectScan" breakthrough. PC-less network compatibility

The fi-8040 comes with the new "DirectScan" function that opens businesses to new options to meet real-world productivity. Compact and equipped with a user-friendly 4.3-inch touch screen, the fi-8040 reliably scans A4 portraits at 40 ppm/80 ipm (200/300 dpi), enables PC-less scans and attaches the scans to emails directly. It also saves scanned data directly to network folders by setting destination storage locations in advance. The setting can be done easily with a web browser for a single unit or with the new "Scanner Central Admin Desktop" software for multiple units.

## Boosted usability and flexibility for any environment

Achieve better user experience with the touch screen on its compact body. Check scanned data before saving, attaching and sending scans, all on the touch screen. Scan a wide variety of documents, including plastic cards and A3, bi-folded, and multi-layered documents without the need for carrier sheets with just a switch to the Manual Feed Mode. Flexible LAN and USB 3.2 connectivity options free users from having to standby a computer when scanning.

#### Optimized high-quality image. More software functionalities.

"PFU Clear Image Capture", a dedicated, image correction technology that redefines the benchmark for high quality image capture. The scanner driver, "PaperStream IP", compatible with standard ISIS and TWAIN applications, is a simplified and user-friendly interface that provides icon visibility for uncomplex setting configurations. The driver automatically produces clear image data, supporting OCR accuracy. Link up with the PaperStream IP, the "PaperStream Capture" to efficiently feed information into organization workflows with automatic utilization of data extracted from barcodes and zonal OCR, further streamlining mundane tasks.

#### RICOH fi-8040

#### **Technical Information**

Technical Information		
Scanner Type	ADF (Automatic Document Feeder)/Manual Feed,	
	Duplex	
Scanning Speed*1		
(A4 Portrait)	Simplex: 40 ppm (200/300 dpi)	
(Color*2/Grayscale*2/	Duplex : 80 ipm (200/300 dpi)	
Monochrome*3)		
Image Sensor Type	CIS x 2 (front x 1, back x 1)	
Light Source	RGB LED x 2 (front x 1, back x 1)	
Optical Resolution	600 dpi	
Output Resolution*4	50 to 600 dpi (adjustable by 1 dpi increments),	
(Color/Grayscale/	1,200 dpi (driver)*5	
Monochrome)	1,200 api (anver) -	
Output Format	Color: 24-bit, Grayscale: 8-bit, Monochrome: 1-bit	
Background Colors	White	
Document Size		
Maximum	216 x 355.6 mm (8.5 x 14 in.)	
Minimum	50.8 x 50.8 mm (2 x 2 in.)	
Long Page Scanning*6		
(Maximum)	5,588 mm (220 in.)	
Paper Weight (Thickness)		
Paper	40 to 209 g/m² (11 to 56 lb)*7	
Plastic Card	0.76 mm (0.0299 in.) or less*8	
ADF Capacity*9*10	50 sheets (A4 80 g/m <sup>2</sup> or Letter 20 lb)	
Expected Daily	-	
Volume*11	6,000 sheets	
Multifeed Detection	Overlap detection (Ultrasonic sensor),	
	Length detection	
Interface	3	
USB	USB 3.2 Gen1x1/USB 3.0/USB 2.0/USB 1.1	
	10BASE-T, 100BASE-TX, 1000BASE-T	
Power Requirements	AC 100 to 240 V ±10 %	
Power Consumption		
Operating Mode	19 W or less	
Sleep Mode	1.9 W or less (Normal mode)	
Auto Standby (Off)	1.5 W Of ICSS (Normal mode)	
Mode	0.15 W or less	
141000		

Operating Environment		
Temperature	5 to 35 °C (41 to 95 °F)	
Relative Humidity	20 to 80% (non-condensing)	
Environmental	ENERGY STAR®, RoHS	
Compliance		
Dimensions*12		
(Width x Depth x	292 x 157 x 143 mm (11.5 x 6.2 x 5.6 in.)	
Height)		
Weight	3.1 kg (6.8 lb)	
Supported	Windows® 11*13, Windows® 10*13, Windows Server®	
Operating System	2022, Windows Server® 2019, Windows Server® 2016	
Software / Drivers	PaperStream IP Driver (TWAIN/TWAIN x64/ISIS),	
	WIA Driver*14, PaperStream Capture, PaperStream	
	ClickScan*15, Software Operation Panel, Error Recovery	
	Guide, ABBYY FineReader for ScanSnap™*15, Scanner	
	Central Admin Server, Scanner Central Admin Desktop	
Image Processing	Multi image output, Automatic color detection, Blank	
Functions*16	page detection, Dynamic threshold (iDTC), Advanced	
	DTC, SDTC, Error diffusion, Dither, Static threshold,	
	De-Screen, Emphasis, Dropout color (None/Red/Green/	
	Blue/White/Saturation/Custom), sRGB output, Split	
	image, De-Skew, Edge filler, Vertical streaks reduction,	
	Cropping, Rotation, Barcode detection (1D&2D),	
	Background pattern removal	
Included Items	ADF paper chute, AC cable, AC adapter, USB cable,	
	Setup DVD-ROM	

#### Options

PaperStream Capture Pro	PA43404-A665	PaperStream Capture Pro
Scan Station (WG)	PA43404-A665	optional license
Carrier Sheets	PA03360-0013	Each package contains 5
		carrier sheets

#### Consumables

Roller Set S	PA03750-0001	Brake Roller	Every 200,000 sheets or
		Pick Roller	one year

<sup>\*1</sup> Scanning speeds may vary due to the system environment. For details, please visit our website at: https://www.pfu.ricoh.com/global/scanners/fi/. \*2 Indicated speeds are from using TIFF CCITT Group 4 compression. \*3 Indicated speeds are from using TIFF CCITT Group 4 compression. \*4 Selectable maximum resolution may vary depending on the length of the scanned document. \*5 Limitations may apply to the size of documents that can be scanned, depending on system environment, when scanning at high resolution (over 600 dpi). \*6 Capable of scanning documents longer than A4 (210 x 297 mm / 8.3 x 11.7 in.) sizes. When using PaperStream IP (TWAIN/ISIS) to scan at 200 dpi, the maximum scanning length is 5,588 mm (220 in.). \*7 Thicknesses of up to 128 to 209 g/m² (34 to 56 lb) can be scanned for A8 (52 x 74 mm / 2.1 x 2.9 in.) sizes. \*8 Multiple cards cannot be set continuously (Note: capable of scanning embossed cards). \*9 Maximum capacity depends on paper weight and may vary. \*10 Capable of setting additional documents while scanning. \*11 Numbers are calculated using scanning speeds and typical hours of scanner use, and are not meant to guarantee daily volume or unit durability. \*12 Excludes the ADF paper chute and stacker. \*13 fi Series scanners do not run with Windows\* 11 and 10 ARM-based PCs. \*14 Functions equivalent to those offered by PaperStream IP may not be available with the Image Scanner for macOS/Linux or VIAD Driver. \*15 Refer to the fi Series Support Site for driver/software downloads and full lineup of all supported operating system versions. \*16 Some functions do not apply when using the \*DirectScan\* function. Refer to the fi Series Support Site for the latest functions.

#### Trademarks

ABBYY¹M FineReader¹M Engine © ABBYY. OCR by ABBYY. ABBYY and FineReader are trademarks of ABBYY Software, Ltd. which may be registered in some jurisdictions. ISIS is a trademark of Open Text. Microsoft, Windows, and Windows Server are trademarks of the Microsoft group of companies. macOS is a trademark of Apple Inc., registered in the U.S. and other countries. Linux is the registered trademark of Linux Torvalds in the U.S. and other countries. Any other products or company names appearing in this document are the trademarks or registered trademarks of the respective companies. Safety Precautions

Be sure to carefully read all safety precautions prior to using this product and use this device as instructed. Do not place this device in wet, moist, steamy, dusty or oily areas. Using this product under such

Be sure to carefully read all safety precautions prior to using this product and use this device as instructed. Do not place this device in wet, moist, steamy, dusty or only areas. Using this product under such conditions may result in electrical shock, fire or damage to this product. Be sure to limit the use of this product to listed power ratings.

ENERGY STAR®

PFU Limited has determined that this product meets the ENERGY STAR® guidelines for energy efficiency. ENERGY STAR® is a registered trademark of the United States.

# **PFU Limited**

RICOH and RICOH logo are registered trademarks of Ricoh Co., Ltd. Other product names are the trademarks or registered trademarks of the respective companies.

Specifications are subject to change without notice. Visit the fi Series website for more information. https://www.pfu.ricoh.com/global/scanners/ © PFU Limited 2023

https://www.pfu.ricoh.com/global/

Page 2 of 2 2023.11 8040-2.0